



Quality Products. Service Excellence.

## Thermostats SKT Series



### Features


- Designed to provide air temperature control and monitoring in cabinets.
- Thermostat NC (Normally Closed) for the control of heaters and heater fans.
- Thermostat NO (Normally Open) for the control of cooling units, or for switching signal transmitters in case of overheating.
- Available in Fahrenheit or Celsius.

### NC - Normally Closed (Red)

- Used in conjunction with heaters.
- Contact opens when rising temperatures reach the set point temperature, shutting heater off.

### NO - Normally open (Blue)

- Used in conjunction with fans.
- Contact closes when rising temperatures reach the set point temperature, turning fan on.



Part No.	Scale	Contact Type	Dimensions	
			Height x Width x Depth	Switching Capacity
SKT011409NC	F°	Normally Closed	2.8 x 1.5 x 1.4	15 A (1) AC 120 V, 10 A (1) AC 250 V
SKT011409NC-C	C°	Normally Closed	2.8 x 1.5 x 1.4	15 A (1) AC 120 V, 10 A (1) AC 250 V
SKT011419NO	F°	Normally Open	2.8 x 1.5 x 1.4	15 A (1) AC 120 V, 10 A (1) AC 250 V
SKT011419NO-C	C°	Normally Open	2.8 x 1.5 x 1.4	15 A (1) AC 120 V, 10 A (1) AC 250 V

Sensor Element:	Thermostatic bi-metal
Switching difference (hysteresis):	+ or - 4°F (+or- 3°K)
Adjustment Range:	30 - 140°F / 0 - 60°C
Noise Suppression:	N (according to VDE 0875)
Connection:	2 pole terminal for AWG 14 (2.5 mm <sup>2</sup> )
Mounting:	Easily installed by clip mounting on 35 or 38mm DIN rail (included)
Housing:	Flame retardant plastic UL94VO
Color:	Gray (SB)
Protection:	IP20
Approval:	UL Recognized Component, cUL Recognized Component, CE

© 2018. Hammond Manufacturing Ltd. All rights reserved.