



Quality Products. Service Excellence.

Rack Mount Basic PDU 1583 Series

15A | Single-Phase 125V | Front and/or Rear Facing 5-15R Outlets

Features



- Designed for power distribution from the front and/or rear of the unit.
- 1U horizontal 19" rackmount installation.
- With lighted on/off switch or red pilot light to indicate power on.
- 6 outlet models include 2 outlets with extra spacing for clearance of most plug in transformers.
- Available in ASA 61 grey or black powder coat finish.
- [Click here for our surge protected version.](#)

Specifications

- Heavy duty 14 gauge wire cord - 14/3 SJT type for extreme temperature ranges and integral molded plug.
- Plug types available are NEMA 5-15P straight blade or NEMA L5-15P locking type.
- Includes 15 Amp, 125 VAC circuit breaker to prevent accidental overload.
- UL/cUL recognized Standard UL1363 file No. E166039 & CSA C22.2 No. 308-14 & CSA C22.2 No. 0.4-04



Gallery



Accessories

- Mounting Hardware
- Rail Depth Adapter Kit

Black Finish

| Illuminated On/Off Switch Part No. | Illuminated Light Only Part No. | Overall Dimensions | | | Number of Outlets | | NEMA Type | | Plug | | Cord Length | Rack Units |
|------------------------------------|---------------------------------|--------------------|-------|-------|-------------------|------|-----------|--------|------------|-----------------|-------------|------------|
| | | Height | Width | Depth | Front | Rear | Outlet | Plug | Blade Type | Rotated Outlets | | |
| 1583H12A1BKX | 1583T12A1BKX | 1.72 | 19.00 | 2.66 | 6 | 6 | 5-15R | 5-15P | Straight | No | 6 ft | 1U |
| 1583H12A1BKXRA | 1583T12A1BKXRA | 1.72 | 19.00 | 2.66 | 6 | 6 | 5-15R | 5-15P | Straight | Yes | 6 ft | 1U |
| 1583H12B1BKX | 1583T12B1BKX | 1.72 | 19.00 | 2.66 | 6 | 6 | 5-15R | 5-15P | Straight | No | 15 ft | 1U |
| 1583H12B1BKXRA | 1583T12B1BKXRA | 1.72 | 19.00 | 2.66 | 6 | 6 | 5-15R | 5-15P | Straight | Yes | 15 ft | 1U |
| 1583H12C1BKX | 1583T12C1BKX | 1.72 | 19.00 | 2.66 | 6 | 6 | 5-15R | L5-15P | Locking | No | 6 ft | 1U |
| 1583H12D1BKX | 1583T12D1BKX | 1.72 | 19.00 | 2.66 | 6 | 6 | 5-15R | L5-15P | Locking | No | 15 ft | 1U |
| 1583H6A1BK | 1583T6A1BK | 1.72 | 19.00 | 2.66 | 0 | 6 | 5-15R | 5-15P | Straight | No | 6 ft | 1U |

| Illuminated On/Off Switch Part No. | Illuminated Light Only Part No. | Overall Dimensions | | | Number of Outlets | | NEMA Type | | Plug Blade Type | Rotated Outlets | Cord Length | Rack Units |
|--|---------------------------------------|--------------------|-------|-------|-------------------|------|-----------|--------|-----------------------|--------------------|----------------|---------------|
| | | Height | Width | Depth | Front | Rear | Outlet | Plug | | | | |
| 1583H6A1BKRA | 1583T6A1BKRA | 1.72 | 19.00 | 2.66 | 0 | 6 | 5-15R | 5-15P | Straight | Yes | 6 ft | 1U |
| 1583H6A1BKX | 1583T6A1BKX | 1.72 | 19.00 | 2.66 | 2 | 4 | 5-15R | 5-15P | Straight | No | 6 ft | 1U |
| 1583H6B1BK | 1583T6B1BK | 1.72 | 19.00 | 2.66 | 0 | 6 | 5-15R | 5-15P | Straight | No | 15 ft | 1U |
| 1583H6B1BKRA | 1583T6B1BKRA | 1.72 | 19.00 | 2.66 | 0 | 6 | 5-15R | 5-15P | Straight | Yes | 15 ft | 1U |
| 1583H6B1BKX | 1583T6B1BKX | 1.72 | 19.00 | 2.66 | 2 | 4 | 5-15R | 5-15P | Straight | No | 15 ft | 1U |
| 1583H6C1BK | 1583T6C1BK | 1.72 | 19.00 | 2.66 | 0 | 6 | 5-15R | L5-15P | Locking | No | 6 ft | 1U |
| 1583H6C1BKRA | 1583T6C1BKRA | 1.72 | 19.00 | 2.66 | 0 | 6 | 5-15R | L5-15P | Locking | Yes | 6 ft | 1U |
| 1583H6C1BKX | 1583T6C1BKX | 1.72 | 19.00 | 2.66 | 2 | 4 | 5-15R | L5-15P | Locking | No | 6 ft | 1U |
| 1583H6D1BK | 1583T6D1BK | 1.72 | 19.00 | 2.66 | 0 | 6 | 5-15R | L5-15P | Locking | No | 15 ft | 1U |
| 1583H6D1BKRA | 1583T6D1BKRA | 1.72 | 19.00 | 2.66 | 0 | 6 | 5-15R | L5-15P | Locking | Yes | 15 ft | 1U |
| 1583H6D1BKX | 1583T6D1BKX | 1.72 | 19.00 | 2.66 | 2 | 4 | 5-15R | L5-15P | Locking | No | 15 ft | 1U |
| 1583H8A1BK | 1583T8A1BK | 1.72 | 19.00 | 2.66 | 0 | 8 | 5-15R | 5-15P | Straight | No | 6 ft | 1U |
| 1583H8B1BK | 1583T8B1BK | 1.72 | 19.00 | 2.66 | 0 | 8 | 5-15R | 5-15P | Straight | No | 15 ft | 1U |
| 1583H8C1BK | 1583T8C1BK | 1.72 | 19.00 | 2.66 | 0 | 8 | 5-15R | L5-15P | Locking | No | 6 ft | 1U |
| 1583H8D1BK | 1583T8D1BK | 1.72 | 19.00 | 2.66 | 0 | 8 | 5-15R | L5-15P | Locking | No | 15 ft | 1U |

ASA 61 Grey Finish

| Illuminated On/Off Switch Part No. | Illuminated Light Only Part No. | Overall Dimensions | | | Number of Outlets | | Outlet NEMA Type | Rotated Outlets | Cord Length | Plug Blade Type | NEMA Plug Type | Rack Units |
|--|---------------------------------------|--------------------|-------|-------|-------------------|------|------------------------|--------------------|----------------|-----------------------|----------------------|---------------|
| | | Height | Width | Depth | Front | Rear | | | | | | |
| 1583H6A1 | 1583T6A1 | 1.72 | 19.00 | 2.66 | 0 | 6 | 5-15R | No | 6 ft | Straight | 5-15P | 1U |
| 1583H6B1 | 1583T6B1 | 1.72 | 19.00 | 2.66 | 0 | 6 | 5-15R | No | 15 ft | Straight | 5-15P | 1U |
| 1583H6C1 | 1583T6C1 | 1.72 | 19.00 | 2.66 | 0 | 6 | 5-15R | No | 6 ft | Locking | L5-15P | 1U |
| 1583H6D1 | 1583T6D1 | 1.72 | 19.00 | 2.66 | 0 | 6 | 5-15R | No | 15 ft | Locking | L5-15P | 1U |
| 1583H8A1 | 1583T8A1 | 1.72 | 19.00 | 2.66 | 0 | 8 | 5-15R | No | 6 ft | Straight | 5-15P | 1U |
| 1583H8B1 | 1583T8B1 | 1.72 | 19.00 | 2.66 | 0 | 8 | 5-15R | No | 15 ft | Straight | 5-15P | 1U |
| 1583H8C1 | 1583T8C1 | 1.72 | 19.00 | 2.66 | 0 | 8 | 5-15R | No | 6 ft | Locking | L5-15P | 1U |
| 1583H8D1 | 1583T8D1 | 1.72 | 19.00 | 2.66 | 0 | 8 | 5-15R | No | 15 ft | Locking | L5-15P | 1U |

Data subject to change without notice

© 2021. Hammond Manufacturing Ltd. All rights reserved.