



*Quality Products. Service Excellence.*

## Linear Amplifier *HL-700 Series* (Circa 1960-1970 - No longer in production)

### Features



- BAND COVERAGE
  - 75 Meter, 40 Meter, 20 Meter, 15 Meter & 10 Meter Amateur Bands
- TUBE COMPLIMENT
  - Choice of either (4) 811A Triodes or (4) 572-B Triodes
  - Operated AB2 - Grounded Grid Service
- MODE AND DUTY CYCLE
  - SSB (700 Watts Input) - dependant on supply voltage.
  - CW (700 Watts Input) - dependant on supply voltage.
- DRIVE POWER
  - 75-100 Watts
- COOLING
  - Forced Air
- ALC
  - None
- TUNING
  - Vernier tuning
  - 0 - 100 dial skirt log for easy resetting
- INPUT CIRCUIT
  - Untuned
- OUTPUT CIRCUIT
  - Pi-Network
- ANTENNA RELAY
  - None (supplied externally) - amplifier is designed to follow an exciter
- METERING
  - (4) Simpson Meters
  - High Voltage, Grid Current, Plate Current & Relative Output
- FINISH
  - Smooth Grey Baked Enamel

*Data subject to change without notice*

© 2019. Hammond Manufacturing Ltd. All rights reserved.