





Quality Products. Service Excellence.

## Hard Wired 170 Series



### Features

- Single winding, does not provide isolation, for use where equipment is already isolated and only voltage change is required.
- Flexible world wide applications, 50 or 60 Hz. operation, step down (230VAC to 115 VAC) or step up (115VAC to 230VAC).
- Connection by flexible leads, 8" minimum length.
- Models 170A, 170B, 170C & 170D are CSA certified (209651)
- Remember - These units do NOT convert line frequency



| Part No. | Capacity | Overall Dimensions |      |      |      |      | Weight |
|----------|----------|--------------------|------|------|------|------|--------|
|          | VA       | A                  | B    | C    | D    | E    | Lbs    |
| 170      | 50       | 2.19               | 2.63 | 2.63 | 1.75 | 1.56 | 2      |
| 170A     | 100      | 2.50               | 3.00 | 3.10 | 2.00 | 1.90 | 3      |
| 170B     | 200      | 3.13               | 3.50 | 3.80 | 2.50 | 2.20 | 4.5    |
| 170C     | 300      | 3.13               | 4.00 | 3.80 | 2.50 | 2.70 | 6      |
| 170D     | 500      | 3.75               | 4.50 | 4.60 | 3.00 | 3.30 | 10     |
| 170E     | 750      | 3.75               | 5.50 | 4.60 | 3.00 | 4.30 | 14     |
| 170F     | 1000     | 3.75               | 5.50 | 4.60 | 3.00 | 4.30 | 14.5   |
| 170G     | 1500     | 4.38               | 6.60 | 5.30 | 3.50 | 5.10 | 22     |
| 170J     | 2000     | 4.38               | 7.50 | 5.30 | 3.50 | 5.91 | 23     |



Data subject to change without notice