

Bonding Wire Jumper *BWJ Serie*

Features



- Constructed with UL Listed components.
- #6 AWG 266 strand copper, MTW/TEW UL1283 type, Green-insulated with a yellow stripe.
- Two holes compression lugs with bolt holes that are 0.281" (7.1 mm) in diameter and spaced 5/8" (15.9 mm) apart.
- Terminated with crimped-on compression lug at one (1) end.
- Mounting hardware included for fastening to either 1/4-20 or 10-32 studs.
- Stick-on grounding symbol for compliance.
- TAA-compliant for GSA Schedule purchases.
- RoHS Compliant.
- Manufactured in North America.



Accesorios

- Thread-Forming Bonding Screw

Part No.	Length	Cable Qty Included	Bolt Hole Qty	Bolt Hole Spacing	Bolt Hole Ø	Wire Gauge	Hardware Included	Quick Disconnecting Terminals
BWJ6A60	60.00	1	2	0.62	0.28	6 AWG	Yes	No
BWJ6A96	96.00	1	2	0.62	0.28	6 AWG	Yes	No
BWJ6A108	108.00	1	2	0.62	0.28	6 AWG	Yes	No
BWJ6A120	120.00	1	2	0.62	0.28	6 AWG	Yes	No
BWJ6A180	180.00	1	2	0.62	0.28	6 AWG	Yes	No
BWJ6A1200	1200.00	1	2	0.62	0.28	6 AWG	Yes	No

Datos sujetos a cambios sin previo aviso.