



hammondmfg.com

## Horizontal Finger Cable Manager *RB-HFM-OS Serie*

REPLACED BY THE RB-HFM SERIES

**Nota:** Esta línea de productos ha sido descatalogada como serie en stock. La información es sólo para referencia. Ha sido sustituida por **RB-HFM Series**. Para obtener asistencia sobre soluciones alternativas, **contacte con Hammond aquí** o llame al: EE.UU. (716) 630-7030, Canadá e Internacional (519) 822-2960.

### Features



- Metal components constructed in 16-gauge steel.
- Three (3) inch length fingers constructed in black plastic.
- Snap-on, hinged door.
- Includes cutouts at rear for cable pass-through.
- Fits standard EIA compliant mounting rails.
- Metal components finished in textured RAL9005 black powder paint.
- Requires mounting hardware.
- RoHS and REACH compliant.



**i** For a double-sided manager, install two (2) managers mounted back-to-back. The rear opening provides a cable pass-thru.

Part of the Rack Basics® line of economy rack solutions.

### Accesorios

- Hardware for Rack Mounting Solutions
- Hook and Loop Cable Straps Pre-Cut 96 Inch

**RACK BASICS®**

A HAMMOND BRAND



Part No.	Height	Overall Dinmensions			Usable Mounting Dimensions	
		Width	Depth	Rack Units	Height	
RB-HFM1	1.72	19.00	4.37	1U	1.75	
RB-HFM2	3.22	19.00	4.37	2U	3.50	

Note that two (2) of the RB-HFM1 cannot be installed on top of each other as the hinged door clip will interfere with the other unit.

### Estimated Cable Fill Capacities

Rack Units	Description	Recommended Cable Fill (50% Fill Ratio)		Maximum Cable Fill (100% Fill Ratio)	
		Cat 6	Cat 6a	Cat 6	Cat 6a
1U	Channel Opening	20	14	40	28
	Finger Opening	18	12	35	24
	Rear Pass Through	20	14	40	28
2U	Channel Opening	49	34	99	69
	Finger Opening	18	12	35	24
	Rear Pass Through	39	27	77	54

*Datos sujetos a cambios sin previo aviso.*

© 2026. Hammond Manufacturing Ltd. Todos los derechos reservados.