

## 2-Post Open Frame Rack *DNRRHDKB Serie*

Load rated to 1,200 lbs (544 kg)

**Note:** This product line has been discontinued as a stocked series on October 31, 2025.

Information is for reference only. It has been replaced with **RB-2PS Series**.

For alternative solution assistance, **contact Hammond here** or call: USA (716) 630-7030, Canada and International (519) 822-2960.



When strength and reliability are the highest priority, be sure to choose the Data/Networking Robust Rack (DNRR) from Hammond Manufacturing. Designed to support your rack-mount infrastructure, regardless of the application, the DNRR includes premium features not found on most other racks.

### Features

- Weighing in at just over 75 lbs., the DNRR Heavy Duty Knockdown Series boasts a 10-gauge steel frame, which is the thickest steel rack on the market. Rack rails are constructed in 10-gauge welded steel. Base angles are constructed in 1/4" steel plates.
- Self-squaring design ships un-assembled (some assembly required).
- Our automated tapping process provides EIA-compliant tapped rails on both the front and back to ensure flexibility when mounting equipment.
  - Includes marked rack unit dividers to aid in equipment mounting.
- When connecting multiple racks together, Hammond provided a 1.25" cable pass-thru. In addition, we added numerous tapped and non-tapped holes for mounting power distribution, cable management and other accessories.
- Includes two (2) pairs of integrated 10-32 ground studs, spaced 5/8" apart. Stud pairs are conveniently located across from each other inside the rail channel. For added convenience, a pair is located near the top of the rack, while the other pair is located at the lower side.
- To keep it looking great, the DNRR undergoes a three-stage paint process, which includes a coat of premium smooth black powder paint. Complies with the Greenguard guidelines for indoor air quality.
- In order to prevent any damage that may occur during transportation, we cover the rails and base of the DNRR with a thick layer of cardboard.
- 1,200 lbs (544 kg) **static load rating**.
- TAA-compliant for federal GSA schedule purchases within the USA.
- RoHS Compliant.
- Manufactured in North America within an ISO 9001:2015 certified facility.

### Galería



### Accesorios

- Rack Panels for Rack Optimization
- Universal Rack Shelf Fixed Steel (Up to 200 lb Capacity)
- Centered Rack Shelf 2U Heavy Duty 200 lb Steel Rack Shelf
- Rack and Cabinet Stem Casters
- Adjustable Rack Mount DIN Rail Kit 2U Steel DIN Rail Panel
- Open Frame Rack and Rack Cabinet Joining Kit
- 10-32 Mounting Hardware
- Hinged Window Rack Security Cover
- Adjustable Rack Shelf
- Keyboard & Equipment Rack Shelf
- Clamping Rack Shelf
- RMU Label Kit (Set of 2)
- Bonding and Grounding
- We Manufacture PDUs and Outlet Strips

Part No.	Overall Dimensions			Rack Units	Mounting Dimensions	
	Height	Width	Depth		Height	Width
DNRR63HDKB	69.13	20.00	15.00	36U	63.00	19.00
DNRR70HDKB	76.13	20.00	15.00	40U	70.00	19.00
DNRR77HDKB	83.13	20.00	15.00	44U	77.00	19.00
DNRR84HDKB	90.13	20.00	15.00	48U	84.00	19.00

Tags: **Relay Rack, H-Frame, Server Rack, Equipment Rack, Network Rack, Skeleton Rack, Telco Rack, Two-Post Rack, knock-down, knock down** *Datos sujetos a cambios sin previo aviso.*

© 2026. Hammond Manufacturing Ltd. Todos los derechos reservados.