

Datawind Filterfans *DPF Serie*

Type 12



Features

- Maintains a UL Tested NEMA Type 12 seal against enclosure
- Externally mounted for space restricted installations such as control panels and IT equipment racks
- 30 degree slope top housing to avoid dust collection
- IEC power connector 6 foot long cable - NEMA 5-15P (115V) and IEC C14 (230V)
- Thermostat with 13 foot long cable allows for placement near heat sensitive locations
- Maintenance LED indication light shows filter status
- Plastic components made from strong, heat resistant (ABS-FR), UL94-V0 fire approved material
- Fluted filter-mat provides longer service life, holding more dust before impeding airflow extending the mean time between maintenance; especially critical for those located in less accessible areas
- Metal housing offered in White (RAL 9003) and Black (RAL 9004) with complementary plastic fan grill
- NOTE - Datawind fan packages pressurize cabinets (push air in) so an exhaust location is needed as a path for heat to escape the cabinet. See table below for exhaust filter options

Accesorios

- Replacement Filters
- Thermostats

Part Number	Part Number	Voltage	Free Flow				Exhaust Filter	Exhaust Filter
			CFM	H	W	D		
White RAL9003	Black RAL9004					Light Gray RAL7035	Black RAL9011	
DPF22000 A115WH	DPF22000 A115BK	115 VAC	38	9.40	6.80	2.76	PFA20000 LG	PFA20000 BK
DPF22000 A230WH	DPF22000 A230BK	230 VAC	38	9.40	6.80	2.76	PFA20000 LG	PFA20000 BK
DPF33000 A115WH	DPF33000 A115BK	115 VAC	152	11.90	9.30	3.30	PFA30000 LG	PFA30000 BK
DPF33000 A230WH	DPF33000 A230BK	230 VAC	152	11.90	9.30	3.30	PFA30000 LG	PFA30000 BK
DPF67000 A115WH	DPF67000 A115BK	115 VAC	560	17.50	14.90	5.50	PFA60000 LG	PFA60000 BK
DPF67000 A230WH	DPF67000 A230BK	230 VAC	560	17.50	14.90	5.50	PFA60000 LG	PFA60000 BK

