

Air to Air Heat Exchangers - Type 12 *PKS12 Serie*



Description

- Designed for indoor applications.
- Air to air heat exchangers provide superior technology when there is a lower surrounding air temperature compared to the target internal temperature (difference of at least 10°C/18°F).
- Closed loop cooling ensures clean enclosure air is recirculated without ever mixing with contaminated ambient air.
- Superior energy efficiency and lower maintenance costs versus air conditioners.

Standards

- Maintains enclosure's NEMA 12 rating
- IP 54
- UR, cUR and CE

Features

- Compact Standard Size: 35"H x 12"W x 11"D
- R134a refrigerant.
- Thermostat control accessible from inside enclosure.
- EMI/RFI suppression meets CE.
- Door contact provision for power down when enclosure door is opened.
- Gasket, mounting kit and template for cutout and drilling are included.
- Can be mounted vertically or horizontally for application flexibility.
- Cover finished in Light Gray (RAL7035) powder coated steel.
- See Manual/Technical Data Sheet for drilling template and full electrical specifications.

Accesorios

- Remote Door Switches
- Gasket Kits

Part No.	Voltage - Frequency	Cooling Capacity		Dimensions			Sample Performance ΔT = 20°C/36°F
		W°C	W°F	H	W	D	
PKS3131A1 15LG	115V 60 Hz	65	36	35.31	11.97	10.65	1300W (4400 BTU)
PKS3131A2 30LG	230V 50/60 Hz	65	36	35.31	11.97	10.65	1300W (4400 BTU)
PKS3131A4 60LG	400/460V 50/60 Hz	65	36	35.31	11.97	10.65	1300W (4400BTU)
PKS3201A1 15LG	115V 60 Hz	100	56	35.31	11.97	10.65	2000W (6800 BTU)
PKS3201A2 30LG	230V 50/60 Hz	100	56	35.31	11.97	10.65	2000W (6800 BTU)

Part No.	Voltage - Frequency	Cooling Capacity		Dimensions			Sample Performanc e
		W/°C	W/°F	H	W	D	ΔT = 20°C/36°F
PKS3201A4 60LG	400/460V 50/60 Hz	100	56	35.31	11.97	10.65	2000W (6800 BTU)
PKS3301A1 15LG	115V 60 Hz	150	83	35.31	11.97	10.65	3000W (10200 BTU)
PKS3301A2 30LG	230V 50/60 Hz	150	83	35.31	11.97	10.65	3000W (10200 BTU)
PKS3301A4 60LG	400/460V 50/60 Hz	150	83	35.31	11.97	10.65	3000W (10200 BTU)
PKS3361A1 15LG	115V 60 Hz	180	100	35.31	11.97	10.65	3600W (12200 BTU)
PKS3361A2 30LG	230V 50/60 Hz	180	100	35.31	11.97	10.65	3600W (12200 BTU)
PKS3361A4 60LG	400/460V 50/60 Hz	180	100	35.31	11.97	10.65	3600W (12200 BTU)

Actual cooling performance based on difference (ΔT) between ambient and target internal temperature.

Tags: air to air, heat exchanger, Type 12, indoor, closed loop, temperature, climate

Datos sujetos a cambios sin previo aviso.

© 2026. Hammond Manufacturing Ltd. Todos los derechos reservados.