

3000-10000 BTU/H Air/Water Heat Exchanger *PWS 7000 Series*

Type 3R, 4, 4X



Description

- Designed to use various water sources to cool enclosures where ambient conditions involve high temperatures, harsh conditions or are subject to frequent wash-down.

Standards

- UL, cUL, and CE
- Complies with
 - NEMA 3R, 4, 4X

Features

- Compatible with chilled water/glycol, tower water and other circulated coolants
- Integrated thermostat & solenoid valve with alarm contact provides automatic temperature control
- Rugged (10 bar) copper tube / aluminum fin heat exchanger with 1/2" barb connection
- Side, door or internal mounting provides complete installation flexibility
- Low noise, maintenance-free design
- Exterior case, galvanized steel construction finish RAL7035 Light Gray

Accesorios

- Remote Door Switches
- Condensate Bottle
- Gasket Kits

Part Number	H	W	D
PWS7102A115N 4LG	19.68	7.88	5.55
PWS7102A230N 4LG	19.68	7.88	5.55
PWS7102A115N 4SS	19.68	7.88	5.55
PWS7102A230N 4SS	19.68	7.88	5.55
PWS7332A115N 4LG	37.40	15.75	7.56
PWS7332A230N 4LG	37.40	15.75	7.56
PWS7332A115N 4SS	37.40	15.75	7.56
PWS7332A230N 4SS	37.40	15.75	7.56

Electrical Data	PWS7102		PWS7332	
	Rated Voltage	115	230	115
Frequency Hz	60	50/60	60	50/60
Power Consumption	95 w	84 w	453 w	385 w
Running Amps	0.8	0.52	3.8	1.95
Connection	Terminal Block		Terminal Block	

Cooling Data	PWS7102	PWS7332
Cooling Capacity Enclosure +95F (+35C) Water +50F (+10C)	3242 BTU/h (950W)	10748 BTU/h (3140 W)

Cooling Data	PWS7102	PWS7332
Adjustable Control Range (Factory setting +95F (+35C))	+46 to +122 F +8 to +50 C	+46 to +122 F +8 to +50 C
Flow Rate at Rated Capacity	53GPH 400L/h	53 GPH 400 L/h
Operating Pressure	14.5 - 145 PSI 1 - 10 bar	14.5 - 145 PSI 1 - 10 bar
Ambient Air Temp	+ 36/158 F +2/+70 C	+ 36/158 F +2/+70 C
Air Volume	153 CFM 260 CM/h	441 CFM 820 CM/h

Tags: **air to water, heat exchanger, Type 3R, Type 4X, outdoor, closed loop, temperature, climate** *Datos sujetos a cambios sin previo aviso.*

© 2026. Hammond Manufacturing Ltd. Todos los derechos reservados.