


## Type 4/12 Mild Steel Multi-Door Freestanding Disconnect Enclosure

### UHD Serie

Hinge Door with Handle (Flange w/ multi-vendor cutout)



### Application

- Designed to accept the following disconnect switches and circuit breakers:
  - **ABB Controls** flange mounted variable depth operating mechanisms for disconnect switches and circuit breakers.
  - **Allen Bradley** 1494V and 1494U variable depth flange mounted disconnect switches and circuit breaker mechanisms.
  - **C-H Westinghouse** type C361 disconnect switches and operator mechanism. Cutler Hammer Type C371 circuit breaker operating mechanisms. Flex-Shaft™ handle operators for circuit breakers.
  - **General Electric** type STDA flange handles and variable depth operating mechanisms for disconnect switches and circuit breakers. Also Spectra-Flex™ cable operators for circuit breakers.
  - **Siemens I-T-E** Max-Flex™ flange mounted variable depth operating handles for disconnect switches and circuit breakers.
  - **Square D** disconnect switches and circuit breakers used with Class 9422 flange mounted variable depth operating mechanisms or cable mechanisms. These enclosures will not receive Class 9422 bracket mounted disconnect devices or class 9422TG1 or TG2 devices.
- Refer to the **Universal Heavy Duty Disconnect Selection Guide**.

### Standards

- UL 508A Type 12, 4
- CSA Type 12, 4
- Complies with
  - NEMA Type 12, 4
  - IEC 60529, IP66
- Appropriate components are required to maintain these standards.

### Construction

- Formed from 10 gauge steel with smooth, continuously welded seams.
- Body stiffeners are provided in the larger enclosures for extra rigidity.
- Flange trough collar (FTC) around door opening excludes liquids and contaminants.
- Heavy duty lifting eyes are anchored into reinforced top corners.
- Removable doors are secured with heavy duty lift off hinges.
- Formed 10 gauge steel inner panels are provided on collar studs.
- Panel supports are provided.
- Center post is removable, providing easy panel installation.
- Heavy duty three point latching mechanism with heavy duty roller ends is provided for ease of door closing.
- Oil resistant gaskets are permanently secured.
- The right-hand door on all enclosures is the main door.
- Main door handle complete with screw defeater and padlock hasp.

- Secondary door handle complete with padlock hasp.
- A mechanical interlock activated by the main door prevents the auxiliary door from being opened first.
- The universal flange cutout provides mounting for disconnect operators by use of the appropriate operator adaptor kit.
- A provision for mounting fluorescent lighting is provided.
- A bonding stud is provided in the door and a grounding stud is provided in the enclosure for each door.
- A literature pocket is provided for the inside of the door.

**Note:**

- Disconnect switches, circuit breakers and operators are not provided with the enclosure, and must be ordered separately from the manufacturer.

**Finish**

- Cover and enclosure are phosphatized and finished in recoatable smooth ANSI 61 gray powder coating.
- Inner panel is finished in white powder coating.

**Accesorios**

- Flange Disconnect Operator Adaptor Kits
- Floor Stand Kit
- Climate Control
- General Accessories
- Door Stop Kit
- Window Kits
- Lighting

**New and improved PDF part drawing files with more detail now available.**

Click part number in table below to access PDF, DXF, and STEP files.

**Single Door**

Part No.	Enclosure			Inner Panel	
	H	W	D	H	W
1UHD722918FT C	72.13	28.75	18.13	60.00	21.75
1UHD723518FT C	72.13	34.75	18.13	60.00	27.75
1UHD724118FT C	72.13	40.75	18.13	60.00	33.75
1UHD844118FT C	84.13	40.75	18.13	72.00	33.75
1UHD844124FT C	84.13	40.75	24.13	72.00	33.75
1UHD904118FT C	90.13	40.75	18.13	78.00	33.75
1UHD904120FT C	90.13	40.75	20.13	78.00	33.75
1UHD904124FT C	90.13	40.75	24.13	78.00	33.75

## 2 Door

Part No.	Enclosure			Inner Panel	
	H	W	D	H	W
2UHD725518FT C	72.13	55.00	18.13	60.00	48.00
2UHD726718FT C	72.13	67.00	18.13	60.00	60.00
2UHD727918FT C	72.13	79.00	18.13	60.00	72.00
2UHD727924FT C	72.13	79.00	24.13	60.00	72.00
2UHD847918FT C	84.13	79.00	18.13	72.00	72.00
2UHD847924FT C	84.13	79.00	24.13	72.00	72.00
2UHD907918FT C	90.13	79.00	18.13	78.00	72.00
2UHD907920FT C	90.13	79.00	20.13	78.00	72.00
2UHD907924FT C	90.13	79.00	24.13	78.00	72.00

## 3 Door

Part No.	Enclosure			Inner Panels		
	H	W	D	H	W1	W2
3UHD721011 8FTC	72.13	100.25	18.13	60.00	27.75	60.00
3UHD721191 8FTC	72.13	118.25	18.13	60.00	33.75	72.00
3UHD841191 8FTC	84.13	118.25	18.13	72.00	33.75	72.00
3UHD841192 4FTC	84.13	118.25	24.13	72.00	33.75	72.00
3UHD901192 4FTC	90.13	118.25	24.13	78.00	33.75	72.00

## 4 Door

Part No.	Enclosure			Inner Panels		
	H	W	D	H	W1	W2
4UHD841571 8FTC	84.13	156.50	18.13	72.00	72.00	72.00
4UHD901571 8FTC	90.13	156.50	18.13	78.00	72.00	72.00

Tags: UHD, two door, three door, four door, freestanding, NEMA 12, Type 12, mild steel, disconnect, circuit breaker, ABB

*Datos sujetos a cambios sin previo aviso.*

