

## Type 4 Two Door Freestanding Enclosure *HN4 FSTD Series*

Continuous Hinge Door with Handle



**Panel  
Sold  
Separately**



### Application

- Designed to house electrical, electronic, hydraulic or pneumatic controls and instruments.
- Provides protection where equipment may be hosed down or otherwise be very wet, or in specific applications.

### Construction

- Formed 12 gauge steel.
- Smooth, continuously welded seams without knockouts, cutouts or holes.
- Heavy duty stainless steel lifting eyelets are provided with reinforcing support angles.
- Doors are supported with heavy gauge continuous hinges.
- Dual Access versions have doors front and back.
- 3-pt padlocking door handle.
- Seamless poured-in place gasket.
- A grounding stud is provided in the enclosure and a bonding stud is provided on the door.
- Center post is removable for easy installation of the inner panel.

### Standards

- UL 508A Type 3R, 4 and 12
- CSA Type 3R, 4 and 12
- Complies with:
  - NEMA Type 3R, 4, 12 and 13
  - IEC 60529, IP66

### Finish

- Cover and enclosure are finished in recoatable smooth ANSI 61 gray powder coating.
- Optional inner panels are available in white powder coating, or unpainted galvanized steel.

### Accessories

- Inner Panels
- Panel Rails
- Door Stop Kit
- Drip Shield Kit
- Window Kits
- Lighting
- Center Panel Supports
- Swing Out Frames
- Top Hat Cable Modules
- Type 12/4, 4X Handle Kits
- Climate Control
- General Accessories

### Single Access

| Enclosure   |       |       |       |                                  |
|-------------|-------|-------|-------|----------------------------------|
| Part No.    | H     | W     | D     | Optional Full Panel <sup>1</sup> |
| HN4FS604818 | 60.00 | 48.00 | 18.00 | 60AWFW                           |
| HN4FS724818 | 72.00 | 48.00 | 18.00 | 72ZWFW                           |
| HN4FS726018 | 72.00 | 60.00 | 18.00 | 72ZXF                            |
| HN4FS727218 | 72.00 | 72.00 | 18.00 | 72ZYFW                           |
| HN4FS904820 | 90.00 | 48.00 | 20.00 | 90BWFW                           |
| HN4FS907220 | 90.00 | 72.00 | 20.00 | 90BYFW                           |
| HN4FS724824 | 72.00 | 48.00 | 24.00 | 72ZWFW                           |
| HN4FS726024 | 72.00 | 60.00 | 24.00 | 72ZXF                            |
| HN4FS727224 | 72.00 | 72.00 | 24.00 | 72ZYFW                           |
| HN4FS907224 | 90.00 | 72.00 | 24.00 | 90BYFW                           |
| HN4FS726036 | 72.00 | 60.00 | 36.00 | 72ZXF                            |
| HN4FS907236 | 90.00 | 72.00 | 36.00 | 90BYFW                           |

<sup>1</sup> Refers to optional full height/full width panels. Depth panels/half height width panels are also available

## Dual Access

| Enclosure     |       |       |       |                                  |
|---------------|-------|-------|-------|----------------------------------|
| Part No.      | H     | W     | D     | Optional Full Panel <sup>1</sup> |
| HN4FS724824DA | 72.00 | 48.00 | 24.00 | 72ZWFW                           |
| HN4FS726024DA | 72.00 | 60.00 | 24.00 | 72ZXF                            |
| HN4FS727224DA | 72.00 | 72.00 | 24.00 | 72ZYFW                           |
| HN4FS907224DA | 90.00 | 72.00 | 24.00 | 90BYFW                           |
| HN4FS726036DA | 72.00 | 60.00 | 36.00 | 72ZXF                            |

<sup>1</sup> Refers to optional full height/full width panels. Depth panels/half height width panels are also available

Tags: **HN4FS, freestanding, steel, type 4, NEMA 4, single access, dual access, outdoor, continuous hinge, handle**

*Datos sujetos a cambios sin previo aviso.*

© 2026. Hammond Manufacturing Ltd. Todos los derechos reservados.