

Type 4 Mild Steel Wallmount Enclosure *HWHK Serie*

Hinge Door with Handle



**Panel
Sold
Separately**



**Handle
Included**



Application

- Designed to enclose electrical and/or electronic equipment and protect against harsh, industrial environments for wallmount applications.
- Provides protection where equipment may be hosed down or otherwise be very wet, or in outdoor applications for full weather protection.
- Ideal for processing plants, utility, outdoor municipal or petro chemical locations where easy yet secure access is required.

Standards

- UL 508A Type 3R, 4 and 12
- CSA Type 3R, 4 and 12
- Complies with
 - NEMA 3R, 4, 12 and 13
 - IEC 60529, IP 66

Construction

- Formed 14 gauge steel bodies and doors.
- Continuously welded seams ground smooth.
- Formed lip on enclosure to exclude flowing liquids and contaminants.
- Powder coated black zinc diecast pad lockable handle with 3 point roller latching system secures door.
- Stainless steel continuous hinge on door may be removed by pulling the stainless steel hinge pin
- Seamless poured-in place gasket.
- Collar studs provided for mounting inner panel.
- Bonding stud provided on door and grounding stud installed in enclosure.

Finish

- Cover and enclosure are finished in recoatable smooth ANSI 61 gray powder coating interior and exterior.

Accessorios

- Additional Inner Panels
- Swing Panel Kit
- Type 12/4, 4X Handle Kits
- Enclosure Stabilizers
- Window Kits
- Lighting
- Perforated Inner Panels
- Door Stop Kit
- Drip Shield Kit
- Floor Stand Kit
- Climate Control
- General Accessories

**New and improved PDF part
drawing files with more detail
now available.**

Click part number in table below
to access PDF, DXF, and STEP files.

Part No.	Overall Dimensions			Optional Inner Panel		
	H	W	D	Part No.	H	W
HW24206GY HK	24.00	20.00	6.00	18P2117	21.00	17.00
HW24246GY HK	24.00	24.00	6.00	18P2121	21.00	21.00
HW24168GY HK	24.00	16.00	8.00	18P2113	21.00	13.00
HW24208GY HK	24.00	20.00	8.00	18P2117	21.00	17.00
HW24248GY HK	24.00	24.00	8.00	18P2121	21.00	21.00
HW24308GY HK	24.00	30.00	8.00	18P2721	27.00	21.00
HW30208GY HK	30.00	20.00	8.00	18P2717	27.00	17.00
HW30248GY HK	30.00	24.00	8.00	18P2721	27.00	21.00
HW30308GY HK	30.00	30.00	8.00	18P2727	27.00	27.00
HW36248GY HK	36.00	24.00	8.00	18P3321	33.00	21.00
HW36308GY HK	36.00	30.00	8.00	18P3327	33.00	27.00
HW42368GY HK	42.00	36.00	8.00	18P3933	39.00	33.00
HW48368GY HK	48.00	36.00	8.00	18P4533	45.00	33.00
HW242010GY HK	24.00	20.00	10.00	18P2117	21.00	17.00
HW302410GY HK	30.00	24.00	10.00	18P2721	27.00	21.00
HW362410GY HK	36.00	24.00	10.00	18P3321	33.00	21.00
HW363010GY HK	36.00	30.00	10.00	18P3327	33.00	27.00
HW423010GY HK	42.00	30.00	10.00	18P3927	39.00	27.00
HW483610GY HK	48.00	36.00	10.00	18P4533	45.00	33.00
HW242412GY HK	24.00	24.00	12.00	18P2121	21.00	21.00
HW302412GY HK	30.00	24.00	12.00	18P2721	27.00	21.00
HW363012GY HK	36.00	30.00	12.00	18P3327	33.00	27.00
HW363612GY HK	36.00	36.00	12.00	18P3333	33.00	33.00
HW423612GY HK	42.00	36.00	12.00	18P3933	39.00	33.00
HW483612GY HK	48.00	36.00	12.00	18P4533	45.00	33.00

Part No.	Overall Dimensions			Optional Inner Panel		
	H	W	D	Part No.	H	W
HW603612GY HK	60.00	36.00	12.00	18P5733	57.00	33.00
HW302416GY HK	30.00	24.00	16.00	18P2721	27.00	21.00
HW363016GY HK	36.00	30.00	16.00	18P3327	33.00	27.00
HW483616GY HK	48.00	36.00	16.00	18P4533	45.00	33.00
HW603616GY HK	60.00	36.00	16.00	18P5733	57.00	33.00

Alternative inner panel options also available.

Tags: **wallmount, Type 4, mild steel, outdoor, processing, utility, petro chemical, hinge door, handle**

Datos sujetos a cambios sin previo aviso.

© 2026. Hammond Manufacturing Ltd. Todos los derechos reservados.