

## Type 4, 4X Polyester Pushbutton Enclosure *PJPB Serie*



### Application

- Designed for use as pushbutton enclosures for 22.5mm or 30.5mm devices.
- Provides outstanding insulation and protection where equipment may be hosed down or be very wet.
- Ideal in applications with high temperatures or highly corrosive environments.

### Standards

- UL 508A Type 1, 2, 3, 4, 4X, 12 and 13
- CSA Type 1, 2, 3, 4, 4X, 12 and 13
- **Complies with**
  - NEMA Type 1, 2, 3, 4, 4X, 12 and 13
  - IEC 60529, IP66

### Construction

- Molded fiberglass polyester enclosure with matching cover is easily punched, cut, or drilled.
- Cover is fastened with captive stainless steel screws in threaded brass inserts.
- Captive oil resistant gasket provides a positive seal.
- Mounting through rear holes on enclosure. Use #8 x 1 inch screw (not included).
- Enhanced UV inhibitors protect against outdoor weathering.
- Operating temperatures between 130°C and -40°C (266°F to -40°F).
- Impact index of 6.78J (5 ft/lb).
- For corrosion resistance information, please refer to table in Technical Information.

### Finish

- Fiberglass polyester material has a gray finish.
- Optional aluminum inner panel natural finish.

### Accesorios

- Hole Plugs

**New and improved PDF part drawing files with more detail now available.**

Click part number in table below to access PDF, DXF, and STEP files.

30.5mm PB	22.5mm PB	# of Holes	Enclosure			Optional Aluminum Panel		
Part No.	Part No.		H	W	D	Part No.	H	W
PJ744P1	PJ744P22 1	1	6.74	3.93	3.88	PJP74	4.00	3.13
PJ744P2	PJ744P22 2	2	6.74	3.93	3.88	PJP74	4.00	3.13
PJ944P3	PJ944P22 3	3	8.99	3.93	3.88	PJP94	6.25	3.13

Tags: **pushbutton, non-metallic, polyester, Type 4X, Type 6P, IP66, 22mm, 30.5mm**

*Datos sujetos a cambios sin previo aviso.*

© 2026. Hammond Manufacturing Ltd. Todos los derechos reservados.