




hammondmfg.com

## Type 4X Stainless Steel Two Door Floormount Enclosure *HN4 FM SS*

### Series

#### Continuous Hinge Door with Handle



### Application

- Designed to house electrical, electronic, hydraulic or pneumatic controls and instruments.
- Provides protection where equipment may be hosed down or otherwise be very wet, or in specific applications where corrosion is a serious problem.

### Construction

- Formed 12 gauge 304 or 316 stainless steel.
- Smooth, continuously welded seams without knockouts, cutouts or holes.
- Heavy duty stainless steel lifting eyebolts are provided with reinforcing support angles.
- Doors are supported with heavy gauge continuous hinges.
- New 3-pt padlocking door handle.
- Seamless poured-in place gasket.
- A grounding stud is provided in the enclosure and a bonding stud is provided on the door.
- Center post is removable for easy installation of the inner panel.
- 12" floor stands are welded to the enclosure.

### Standards

- UL 508A Type 3R, 4X and 12
- CSA Type 3R, 4X and 12
- Complies with:
  - NEMA Type 3R, 4X, 12 and 13
  - IEC 60529, IP66

### Finish

- Cover and enclosure are natural stainless steel with a smooth brushed finish.
- Removable 10 gauge inner panel is finished in white powder coating.

### Accessories

- Additional Inner Panels
- Barrier Kits for Type 4 Floormount
- Drip Shield Kit
- Window Kits
- Lighting
- Door Stop Kit
- Mechanical Interlock
- Type 12/4, 4X Handle Kits
- Climate Control
- General Accessories

**New and improved PDF part drawing files with more detail now available.**

Click part number in table below to access PDF, DXF, and STEP files.

304 S.S. Part Number	316 S.S. Part Number	Enclosure			Panel	
		H	W	D	H	W
HN4FM60481 2SS	HN4FM60481 2S16	60.13	48.06	12.69	56.00	44.00
HN4FM60481 8SS	HN4FM60481 8S16	60.13	48.06	18.69	56.00	44.00
HN4FM60601 2SS	HN4FM60601 2S16	60.13	60.06	12.69	56.00	56.00
HN4FM60601 8SS	HN4FM60601 8S16	60.13	60.06	18.69	56.00	56.00
HN4FM72601 2SS	HN4FM72601 2S16	72.13	60.06	12.69	68.00	56.00
HN4FM72601 8SS	HN4FM72601 8S16	72.13	60.06	18.69	68.00	56.00
HN4FM72721 2SS	HN4FM72721 2S16	72.13	72.06	12.69	68.00	68.00
HN4FM72721 8SS	HN4FM72721 8S16	72.13	72.06	18.69	68.00	68.00
HN4FM72722 4SS	HN4FM72722 4S16	72.13	72.06	24.69	68.00	68.00

Tags: **HN4FM, floormount, two door, stainless steel, Type 4X, NEMA 4X, instrument, hydraulic, pneumatic, 304, 316, continuous hinge, handle** *Datos sujetos a cambios sin previo aviso.*

© 2026. Hammond Manufacturing Ltd. Todos los derechos reservados.