

## Type 4X Stainless Steel Freestanding Enclosure *HN4 FS SS Series*

Continuous Hinge Door with Handle



**Panel  
Sold  
Separately**



### Application

- Designed to house electrical, electronic, hydraulic or pneumatic controls with provision for panel mounting or rack mounting of equipment.
- Provides protection where equipment may be hosed down or otherwise be very wet, or in specific applications where corrosion is a serious problem.
- A variety of inner panels, rack mounting rails and swing out frames are available to provide flexibility in mounting arrangements.

### Construction

- Formed 12 gauge 304 stainless steel.
- Smooth, continuously welded seams without knockouts, cutouts or holes.
- Heavy duty stainless steel lifting eyebolts are provided with reinforcing support angles.
- Doors are supported with heavy gauge continuous hinges.
- New 3-pt padlocking door handle.
- Seamless poured-in-place gasket.
- A grounding stud is provided in the enclosure and a bonding stud is provided on the door.
- Mounting channels are welded on the inside of the enclosure for mounting of optional inner panels or rack equipment rails.

### Standards

- UL 508A Type 3R, 4X and 12
- CSA Type 3R, 4X and 12
- Complies with:
  - NEMA Type 3R, 4X, 12 and 3
  - IEC 60529, IP66

### Finish

- Cover and enclosure are natural stainless steel with a smooth brushed finish.
- Optional inner panels are finished in white powder paint.



We are looking at adding a rack mounting solution similar to this enclosure. [Click here to provide your input.](#)

### Accesorios

- Inner Panels
- Swing Out Frames
- Drip Shield Kit
- Window Kits
- Lighting
- Panel Rails
- Door Stop Kit
- Type 12/4, 4X Handle Kits
- Climate Control
- General Accessories

# New and improved PDF part drawing files with more detail now available.

Click part number in table below to access PDF, DXF, and STEP files.

## Single Access

304 S.S. Part No.	316 S.S. Part No.	H	Enclosure		Optional Full Size Panel
			W	D	
HN4FS602418S	HN4FS602418S1	60.06	24.06	18.06	60TWF
S	6				
HN4FS722418S	HN4FS722418S1	72.06	24.06	18.06	72WF
S	6				
HN4FS723018S	HN4FS723018S1	72.06	30.06	18.06	72XF
S	6				
HN4FS723618S	HN4FS723618S1	72.06	36.06	18.06	72YF
S	6				
HN4FS902420S	HN4FS902420S1	90.06	24.06	20.06	90YWF
S	6				
HN4FS903620S	HN4FS903620S1	90.06	36.06	20.06	90YF
S	6				
HN4FS603624S	HN4FS603624S1	60.06	36.06	24.06	60TYF
S	6				
HN4FS722424S	HN4FS722424S1	72.06	24.06	24.06	72WF
S	6				
HN4FS723024S	HN4FS723024S1	72.06	30.06	24.06	72XF
S	6				
HN4FS723624S	HN4FS723624S1	72.06	36.06	24.06	72YF
S	6				
HN4FS903624S	HN4FS903624S1	90.06	36.06	24.06	90YF
S	6				
HN4FS723630S	HN4FS723630S1	72.06	36.06	30.06	72YF
S	6				
HN4FS723636S	HN4FS723636S1	72.06	36.06	36.06	72YF
S	6				
HN4FS903636S	HN4FS903636S1	90.06	36.06	36.06	90YF
S	6				

Alternative inner panel options also available.

## Dual Access

304 S.S. Part No.	316 S.S. Part No.	H	Enclosure		Optional Full Size Inner Panel
			W	D	
HN4FS722424D	HN4FS722424D	72.06	24.06	24.06	72WF
ASS	S16				
HN4FS723024D	HN4FS723024D	72.06	30.06	24.06	72XF
ASS	S16				
HN4FS723624D	HN4FS723624D	72.06	36.06	24.06	72YF
ASS	S16				
HN4FS903624D	HN4FS903624D	90.06	36.06	24.06	90YF
ASS	S16				
HN4FS722430D	HN4FS722430D	72.06	24.06	30.06	72WF
ASS	S16				
HN4FS722436D	HN4FS722436D	72.06	24.06	36.06	72WF
ASS	S16				

304 S.S. Part No.	316 S.S. Part No.	H	Enclosure W D		Optional Full Size Inner Panel
HN4FS723636D ASS	HN4FS723636D S16	72.06	36.06	36.06	72YFW
HN4FS903636D ASS	HN4FS903636D S16	90.06	36.06	36.06	90YFW

Alternative inner panel options also available.

Tags: **HN4FS, freestanding, stainless, stainless steel, 304, 316, control box, Type 4X, NEMA 4X, continuous hinge, handle** *Datos sujetos a cambios sin previo aviso.*

© 2026. Hammond Manufacturing Ltd. Todos los derechos reservados.