



*Productos de calidad. Excelencia en el servicio.*

## Clear Polycarbonate Lids For 1554/1555 Series 1554-1555LID Serie

### Key Features:



- Replacement lids for 1554 and 1555 series enclosures.
  - NOTE: Replacement clear lids are not styled like standard 1555 lids, but are compatible with 1555 bases.
- When installed properly in conjunction with screws and gasket, lids are designed to meet NEMA Type 4, 4X, 6, 6P, 12 & 13 ratings which meet and exceed IP ratings up to and including IP68. (Except 1554/55 V size which is 4, 4X only.)
- Polycarbonate material is UV stabilized for outdoor use. Clear lids carry a UL94V-0 rating.
- Recommended operating temperature: -40°C to +110°C (-40°F to +230°F).
  - Customers should conduct their own testing to determine suitability for any specific application.
- **Replacement lids do not include screws or gaskets.** Please see **1554 Series** or **1555 Series** pages for compatible accessories.



### Lid Compatibility

Clear Lid	Compatible 1554, 1555 Sizes	Lid Length	Lid Width	Lid Height
1554ACL	A	52	50	15
1554BCL	B	65	65	15
1554CCL	C, D	120	65	15
1554ECL	E, EE	90	90	15
1554FCL	F, FL, G	120	90	15
1554HCL	H, HL, T	180	120	15
1554JCL	J, JL, K	160	90	15
1554LCL	L, LA	105	105	15
1554NCL	N, NL, P	120	120	15
1554QCL	Q, QA	140	140	15
1554RCL	R, RL, S	160	160	15
1554UCL	U, UL, UA	200	120	15
1554VCL	V	240	160	20
1554VACL	VA, VAL, VB	240	160	20
1554WCL	W, WA	180	180	15
1554XCL	X	299	220	20
1554XACL	XA	299	220	50
1554YCL	Y	299	240	25

Clear Lid	Compatible 1554, 1555 Sizes	Lid Length	Lid Width	Lid Height
1554YACL	YA	299	240	50

Tags: **1554, 1555, polycarbonate, clear, lid, clear cover, accessory**

*Datos sujetos a cambios sin previo avisc*

© 2026. Hammond Manufacturing Ltd. Todos los derechos reservados.