

## Type 4, 4X Glass Reinforced Polyester Enclosures *1590ZGRPBK Serie*

Watertight, Thick Wall, NEMA 4X, IP66, UL Listed

### Key Features:



- Molded from black glass reinforced polyester. Smooth finish.
- Heavy duty thick wall design.
- Includes gasketed lid with two piece tongue and groove construction.
- C UL & UL listed under file #E65324.
- Rated IP66. Certified to NEMA 4, 4X standards per UL 508A.
- Enclosures have an impact rating of IK09 in conformity with IEC 62208 and IEC 62262.
- Recommended operating temperature is -40°C to +100°C (-40°F to +212°F).
- Lid contains self-captivated stainless steel screws.
- Gasket material is silicone sponge.
- Easy wall mounting via through holes located outside of the gasket channel.
- Internal mounting shelf for bonding/mounting nuts molded in.
- Optional 16 gauge galvanized steel inner panels available.



### Photo Features

Internal mounting shelf accepts inner panels or PC boards.

Lid screws become captive once installed in lid.

Wall-mounting holes are located outside the gasket perimeter.



### Accessories

Optional hinge kit, part number **1427HKBK**



- Molded from tough polyester
- Includes 12x stainless steel M4 screws and 8x o-rings
- Mounting template included
- Note: with hinges installed, all four lid screws are required to maintain a proper seal

Part Number	Length	Width	Assembled	Enclosure	Lid	Inner Panel	Extra Lid Screws	Extra Panel Screws
			Depth	Depth	Depth			
1590ZGRP081BK	80	75	56	41	15	1590ZGRP081PL	SC583-50	SCGM4-50
1590ZGRP084BK	80	75	75	61	15	1590ZGRP081PL	SC583-50	SCGM4-50
1590ZGRP082BK	110	75	56	41	15	1590ZGRP082PL	SC583-50	SCGM4-50
1590ZGRP121BK	122	120	91	65	26	1590ZGRP121PL	SC570-20	SCGM6GRP-20
1590ZGRP083BK	160	75	56	42	15	1590ZGRP083PL	SC583-50	SCGM4-50
1590ZGRP161BK	160	160	90	70	20	1590ZGRP161PL	SC570-20	SCGM6GRP-20
1590ZGRP131BK	191	75	57	42	16	1590ZGRP131PL	SC583-50	SCGM4-50
1590ZGRP123BK	220	120	90	65	25	1590ZGRP123PL	SC570-20	SCGM6GRP-20
1590ZGRP234BK	255	250	121	96	25	1590ZGRP234PL	SC570-20	SCGM6GRP-20
1590ZGRP235BK	255	250	161	96	66	1590ZGRP234PL	SC571-12	SCGM6GRP-20
1590ZGRP162BK	261	160	90	70	20	1590ZGRP162PL	SC570-20	SCGM6GRP-20
1590ZGRP163BK	360	160	91	72	20	1590ZGRP163PL	SC570-20	SCGM6GRP-20
1590ZGRP243BK	400	250	120	95	25	1590ZGRP243PL	SC570-20	SCGM6GRP-20
1590ZGRP244BK	400	250	160	96	65	1590ZGRP243PL	SC571-12	SCGM6GRP-20
1590ZGRP253BK	400	405	121	95	26	1590ZGRP253PL	SC570-20	SCGM6GRP-20
1590ZGRP263BK	601	250	121	96	26	1590ZGRP263PL	SC570-20	SCGM6GRP-20
1590ZGRP264BK	601	250	161	96	65	1590ZGRP263PL	SC571-12	SCGM6GRP-20

