



Productos de calidad. Excelencia en el servicio.

Thick-Wall Plastic Enclosures w/ EMI/ RFI Shielding 1594R Serie

EMI/ RFI Copper Conductive Coating Inside

Key Features:



- Rugged electronic instrument enclosures, ideally suited for mounting printed circuit boards.
- Heavy duty, thick wall design with an average wall thickness of .13" (3.3 mm).
- Molded from flame retardant ABS plastic (material carries a UL flammability rating of 94V-0).
- Interior of each enclosure part is specially masked and sprayed with an RFI/EMI copper conductive coating (see photo above).
- Coating manufacturer specifies an attenuation of more than 75 db from 1 Mhz. to 1 Ghz.
- Designed to meet IP54.
- Countersunk lid is secured with four M3 x 0.5 - 0.71" (18 mm) long, Philips machine screws threaded into integral brass bushings. Perfect for applications with repetitive assembly and disassembly are required.
- Stocked in black with matte textured finish.



For non-shielded applications, try series 1594 (general purpose and water-tight options)



Enclosures

| Part Number | Color | Length | Width | Enclosure Depth (Less Lid) |
|-------------|-------|--------|-------|----------------------------|
| 1594RABK | Black | 56 | 56 | 28 |
| 1594RBBK | Black | 81 | 56 | 28 |
| 1594RCBK | Black | 104 | 66 | 33 |
| 1594RDBK | Black | 132 | 66 | 43 |
| 1594REBK | Black | 168 | 107 | 53 |

Tags: plastic, ABS, heavy duty, thick wall, multipurpose, PCB, copper coated, EMI, RFI, shielded *Datos sujetos a cambios sin previo aviso*

