



Enclosures can be Factory Modified ( Milling, Drilling, Printing etc.)  
 Contact Factory [mjm@hammondmfg.com](mailto:mjm@hammondmfg.com) for quotes  
 Solid models of this enclosure available in STEP or IGES.  
 (Part number and text placement/orientation on our products are subject to change,  
 we do not recommend using them as a locating reference for modification purposes)

<b>NOTE</b>	
Purchased assembly includes case, cover, 4 cover screws, and 4 rubber feet. Case made from 12 Gauge aluminum (.081"), Top made from 14 Gauge aluminum (.064").	
<b>Recommended screw torque 150-175 cN-m (13.3-15.5 lbf-in)</b>	

<b>1456</b>	
<b>1456CE2 Regular Enclosure</b>	
Beige Top / Blue Case	1456CE2WHBU
Black Top / Blue Case	1456CE2BKBU
Black Top / Black Case	1456CE2BKBK
<b>ACCESSORIES</b>	
Natural Finish Cover Screws (Pkg 6) [6-32 x 1/4" Self-Tapping Screws]	1421J6
Black Cover Screws (Pkg 6) [6-32 x 1/4" Self-Tapping Screws]	1421J6BK
Rubber Feet [0.5 x 0.5" Self-adhesive] (Pkg 24)	1421T3

**HAMMOND MANUFACTURING**

**1456CE2**

[www.hammondmfg.com](http://www.hammondmfg.com)

**Dimensions:**  
 mm  
 [inches]