



ELECTRICAL DATA:		
TESTS	CONDITIONS	ACCEPTANCE CRITERIA
Iex	@ 11V, 400Hz, PIN 1 - PIN 4	5mA Max.
Sec. N.L.V	@ 11V, 400Hz, PIN 1 - PIN 4	
	PIN 5 - PIN 6 =	5.500V ±2%
	PIN 7 - PIN 8 =	5.500V ±2%
DCR	@ 20°C, PIN 1 - PIN 4 =	95.18 Ω ±15%
	@ 20°C, PIN 5 - PIN 6 =	27.71 Ω ±15%
	@ 20°C, PIN 7 - PIN 8 =	27.71 Ω ±15%
HIPOT	PRIMARY - SECONDARY	250V, 60Hz, 1 SEC

REV.#	REVISION	DATE	HAMMOND ELECTRONIC DIVISION		
0	RELEASED.	C.I. 10/11/22	52 RANKIN PLACE, WATERLOO, ONTARIO, N2J 3Z5		
			PH # (519) 886-6181 FAX # (519) 886-9540		
			DWG. BY: C. ILIE	CHK'D BY:	TITLE: P.C. BOARD MOUNT AUDIO TRANSFORMER
			DATE: 10/11/22	APP'D. BY:	DWG. NO. 149G
			DIMENSIONS: IN(X) MM()		