



LABEL:



PRIMARY: TER 1 - TER 2: 240V 60 HZ
 SECONDARY: WHT - WHT 2000V @ 2.5A
 5.0KVA
 SHIELD: GRN
 MADE IN CANADA DATE

ELECTRICAL DATA:

TESTS	CONDITIONS	ACCEPTANCE CRITERIA
Sec. N.L.V	@ 240V, 60Hz, TER 1 - TER 2	
	WHT - WHT	2046.0 V ±3%
POLARITY		
DCR	TER 1 - TER 2	0.056 ±20%
IN OHMS	WHT - WHT	3.24 ±20%
HIPO		
	PRIMARY - CORE	2000V, 60Hz, 1 SEC
	SECONDARY - CORE	5000V, 60Hz, 1 SEC
	PRIMARY - SECONDARY	5000V, 60Hz, 1 SEC

PROPERTY AND COPYRIGHT NOTICE

THIS DRAWING AND THE INFORMATION IT CONVEYS ARE THE PROPERTY OF HAMMOND MANUFACTURING. IT MAY NOT BE REPRODUCED, TRANSMITTED OR USED IN ANY MANNER WHATSOEVER WITHOUT THE WRITTEN PERMISSION OF HAMMOND MANUFACTURING.

REV	NOTES	BY	DATE	REV	NOTES	BY	DATE

HAMMOND MANUFACTURING

ELECTRONIC DIVISION
 52 RANKIN PLACE,
 WATERLOO, ONTARIO, N2J 3Z5
 PHONE: 519.886.6181 FAX: 519.886.9540

5KVA POWER TRANSFORMER

DRAWN C. BACIK	DATE 05/08/15	NUMBER
APPROVED	DATE	PWDP13059