



Enclosures can be Factory Modified (Milling, Drilling, Printing etc.)
 Contact Factory (modshop@hammondmfg.com) for quotes
 Solid models of this enclosure available in .stp or .x_t
 (Part number and text placement/orientation on our products are subject to change,
 we do not recommend using them as a locating reference for modification purposes)

| NOTE | |
|--|-------------|
| Purchased assembly includes box, lid, string gasket, 4 PCB screws, and 4 lid screws. | |
| Recommended Torque : (43-50) Ozf.in / (30-35) cN.m | |
| RP Enclosure | |
| General Purpose ABS Light Grey (UL94 HB) | RP1195BF |
| General Purpose ABS Light Grey with Polycarbonate Clear Lid (UL94 HB) | RP1195CBF |
| Polycarbonate Off-White (UL94-V2) | RP1190BF |
| Polycarbonate Off-White with Clear Lid (UL94-V2) | RP1190CBF |
| ACCESSORIES | |
| Lid Screw (M3.5-0.6 X 10mm) (50 Pkg) | SC619-50 |
| PCB Screw (M3 X 6mm Self-tapping) (50 Pkg) | SC622-50 |
| General Purpose ABS Black Inner Panel 3mm Thick | STC117 |
| Metal Inner Panel 1mm Thick | STA117 |
| String Gasket EPDM Grey (2 Pkg) | RP117GASKET |

HAMMOND MANUFACTURING
 RP119 BF
www.hammondmfg.com

Dimensions:
 mm
 [inches]