



Des produits de qualité. L'excellence du service.

Panneaux pour bâtis en acier perforés Série PPFS

Caractéristiques



- Construction en acier de calibre 16.
- S'adapte aux rails standard conformes à la norme EIA.
- Procure un taux de ventilation de 25 % à travers le panneau.
- Revêtement lisse en poudre.
- Conforme à la réglementation TAA pour les achats dans le cadre du programme de la GSA.
- Conforme à la directive RoHS.
- Fabriqués en Amérique du Nord.

Accessoires




- quincaillerie d'assemblage



We are making changes to the design of this product.

We are enclosing the rack mounting holes and rounding all edges.

Old Design (Left) | New Design (Right)



Part No.	Part No.	Usable Mounting Dimensions	
		Rack Units	Height
RAL9005 Semi-Gloss Black	RAL7035 Semi-Gloss Light Gray		
PPFS19001BK2	PPFS19001LG2	1U	1.75
PPFS19003BK2	PPFS19003LG2	2U	3.50
PPFS19005BK2	PPFS19005LG2	3U	5.25
PPFS19007BK2	PPFS19007LG2	4U	7.00
PPFS19008BK2	PPFS19008LG2	5U	8.75
PPFS19010BK2	PPFS19010LG2	6U	10.50

Les données sont sujettes à changement sans préavis